

# AMERICAN PANEL MODULAR BLAST CHILLERS

MODEL NUMBER	TYPE	MAX. RACK SIZE	CHILLING <sup>1</sup> [LBS]	FREEZING <sup>2</sup> [LBS]	REF. CAPACITY <sup>3</sup> [BTU/HOUR]	REF. SYSTEM	ELECTRICAL SUPPLY	INSTALLED DIMENSIONS WxDxH <sup>4</sup>	MECHANICAL CABINET SHIPPING DIM. WxDxH	SHIPPING WEIGHT [LBS]	AP COND. UNIT	COND. UNIT AIR COOLED	COND. UNIT WATER COOLED
AP20BC-1T	BLAST CHILLER	(1) 26" x 32" x 73.5"	200	N/A	28000	MEDIUM TEMP	208 VAC, 8.22A, 1PH, 60HZ ,15A CIRCUIT	51" x 44" x 88"	(1) 46 1/2" x 52 1/2" x 87" (1) 86"x66"x46"	1,588	RCU4BC	BCH0045M*ACZX04	ZWN045X6*
AP20BC-2T	BLAST CHILLER	(2) 26" x 32" x 73.5"	400	N/A	56000	MEDIUM TEMP	208 VAC, 15.5A, 1PH, 60HZ ,20A CIRCUIT	51" x 82" x 88"	(1) 46 1/2" x 52 1/2" x 87" (1) 86"x66"x60"	2,180	RCU7BC	BCH0076M*ACDX0	SWN0760M6*
AP20BC-3T	BLAST CHILLER	(3) 26" x 32" x 73.5"	600	N/A	84000	MEDIUM TEMP	208 VAC, 22.7A, 1PH, 60HZ ,30A CIRCUIT	51" x 134" x 89"	(2) 46 1/2" x 52 1/2" x 87" (1) 86"x66"x74"	3,138	RCU12BC	BCH0120M*ACDX0	WS1200M6*
AP20BCF-1T	BLAST CHILLER & SHOCK FREEZER	(1) 26" x 32" x 73.5"	200	120	28000	MEDIUM / LOW TEMP	208 VAC, 8.22A, 1PH, 60HZ ,15A CIRCUIT	51" x 44" x 88"	(1) 46 1/2" x 52 1/2" x 87" (1) 86"x66"x46"	1,588	RCU3BCF	BBT0301M6*AP	WS0301M6*AP
AP20BCF-2T	BLAST CHILLER & SHOCK FREEZER	(2) 26" x 32" x 73.5"	400	120	56000	MEDIUM / LOW TEMP	208 VAC, 15.5A, 1PH, 60HZ ,20A CIRCUIT	51" x 82" x 88"	(1) 46 1/2" x 52 1/2" x 87" (1) 86"x66"x60"	2,180	RCU7BCF	BCH0076M*ABXX0	WS0751M6*AP
AP20BCF-3T	BLAST CHILLER & SHOCK FREEZER	(3) 26" x 32" x 73.5"	600	180	84000	MEDIUM / LOW TEMP	208 VAC, 22.7A, 1PH, 60HZ ,30A CIRCUIT	51" x 134" x 89"	(2) 46 1/2" x 52 1/2" x 87" (1) 86"x66"x74"	3,138	RCU12BCF	BLV120BM6*AP	WS1200M6*AP
AP26BC-1T	BLAST CHILLER	(1) 26" x 36" x 73.5"	260	N/A	34000	MEDIUM TEMP	208 VAC, 8.22A, 1PH, 60HZ ,15A CIRCUIT	55" x 48" x 88"	(1) 46 1/2" x 52 1/2" x 87" (1) 86"x66"x46"	1,675	RCU.6.5BC	BCH0060M*ACZX04	ZWN060X6*
AP26BC-1T-CP SM	BLAST CHILLER	(1) 35" x 36" x 73.5"	260	N/A	34000	MEDIUM TEMP	208 VAC, 8.22A, 1PH, 60HZ ,15A CIRCUIT	61" x 38" x 83"	(1) 46 1/2" x 52 1/2" x 87" N/A	600	RCU.6.5BC	BCH0060M*ACZX04	ZWN060X6*
AP26BC-2T	BLAST CHILLER	(2) 26" x 36" x 73.5"	520	N/A	68000	MEDIUM TEMP	208 VAC, 15.5A, 1PH, 60HZ ,20A CIRCUIT	55" x 90" x 88"	(1) 46 1/2" x 52 1/2" x 87" (1) 92"x66"x60"	2,328	RCU12BC	BCH0120M*ACDX0	WS1200M6*
AP26BC-2T-CP SM	BLAST CHILLER	(2) 35" x 36" x 73.5"	520	N/A	68000	MEDIUM TEMP	208 VAC, 15.5A, 1PH, 60HZ ,20A CIRCUIT	61" x 80" x 83"	(1) 46 1/2" x 52 1/2" x 87" N/A	950	RCU12BC	BCH0120M*ACDX0	WS1200M6*
AP26BC-3T	BLAST CHILLER	(3) 26" x 36" x 73.5"	780	N/A	102000	MEDIUM TEMP	208 VAC, 22.7A, 1PH, 60HZ ,30A CIRCUIT	55" x 146" x 89"	(2) 46 1/2" x 52 1/2" x 87" (1) 86"x66"x74"	3,349	RCU15BC	BCH0150M*ACDC06	SWN1500M6*
AP26BC-3T-CP SM	BLAST CHILLER	(3) 35" x 36" x 73.5"	780	N/A	102000	MEDIUM TEMP	208 VAC, 22.7A, 1PH, 60HZ ,30A CIRCUIT	61" x 122" x 83"	(2) 46 1/2" x 52 1/2" x 87" N/A	1,601	RCU15BC	BCH0150M*ACDC06	SWN1500M6*
AP26BCF-1T	BLAST CHILLER & SHOCK FREEZER	(1) 26" x 36" x 73.5"	260	156	34000	MEDIUM / LOW TEMP	208 VAC, 8.22A, 1PH, 60HZ ,15A CIRCUIT	55" x 48" x 88"	(1) 46 1/2" x 52 1/2" x 87" (1) 86"x66"x46"	1,675	RCU6BCF	BCH0056M*ABXX0	WS0750M6**SP
AP26BCF-1T-CP SM	BLAST CHILLER & SHOCK FREEZER	(1) 35" x 36" x 73.5"	260	156	34000	MEDIUM / LOW TEMP	208 VAC, 8.22A, 1PH, 60HZ ,15A CIRCUIT	61" x 38" x 83"	(1) 46 1/2" x 52 1/2" x 87" N/A	600	RCU6BCF	BCH0056M*ABXX0	WS0750M6**SP
AP26BCF-2T	BLAST CHILLER & SHOCK FREEZER	(2) 26" x 36" x 73.5"	520	312	68000	MEDIUM / LOW TEMP	208 VAC, 15.5A, 1PH, 60HZ ,20A CIRCUIT	55" x 90" x 88"	(1) 46 1/2" x 52 1/2" x 87" (1) 92"x66"x60"	2,328	RCU12BCF	BLV120BM6*AP	WS1200M6*AP
AP26BCF-2T-CP SM	BLAST CHILLER & SHOCK FREEZER	(2) 35" x 36" x 73.5"	520	312	68000	MEDIUM / LOW TEMP	208 VAC, 15.5A, 1PH, 60HZ ,20A CIRCUIT	61" x 80" x 83"	(1) 46 1/2" x 52 1/2" x 87" N/A	950	RCU12BCF	BLV120BM6*AP	WS1200M6*AP
AP26BCF-3T	BLAST CHILLER & SHOCK FREEZER	(3) 26" x 36" x 73.5"	780	468	102000	MEDIUM TEMP	208 VAC, 22.7A, 1PH, 60HZ ,30A CIRCUIT	55" x 146" x 89"	(2) 46 1/2" x 52 1/2" x 87" (1) 86"x66"x74"	3,349	RCU22BCF	BCV0220M*ABXX0	WS2200M6*AP
AP26BCF-3T-CP SM	BLAST CHILLER & SHOCK FREEZER	(3) 35" x 36" x 73.5"	780	468	102000	MEDIUM / LOW TEMP	208 VAC, 22.7A, 1PH, 60HZ ,30A CIRCUIT	61" x 122" x 83"	(2) 46 1/2" x 52 1/2" x 87" N/A	1,601	RCU22BCF	BCV0220M*ABXX0	WS2200M6*AP
AP36BC-1T	BLAST CHILLER	(1) 31" x 38" x 73.5"	360	N/A	44000	MEDIUM TEMP	208 VAC, 8.22A, 1PH, 60HZ ,15A CIRCUIT	60" x 50" x 88"	(1) 46 1/2" x 52 1/2" x 87" (1) 86"x66"x46"	1,741	RCU7BC	BCH0076M*ACDX0	SWN0760M6*
AP36BC-2T	BLAST CHILLER	(2) 31" x 38" x 73.5"	720	N/A	88000	MEDIUM TEMP	208 VAC, 15.5A, 1PH, 60HZ ,20A CIRCUIT	60" x 94" x 88"	(1) 46 1/2" x 52 1/2" x 87" (1) 96"x66"x60"	2,429	RCU12BC	BCH0120M*ACDX0	WS1200M6*
AP36BC-3T	BLAST CHILLER	(3) 31" x 38" x 73.5"	1080	N/A	132000	MEDIUM TEMP	208 VAC, 22.7A, 1PH, 60HZ ,30A CIRCUIT	60" x 152" x 89"	(2) 46 1/2" x 52 1/2" x 87" (1) 86"x66"x74"	3,484	RCU25BC	BCV0250M*ACDX0	WS2500M6*
AP36BCF-1T	BLAST CHILLER & SHOCK FREEZER	(1) 31" x 38" x 73.5"	360	216	44000	MEDIUM / LOW TEMP	208 VAC, 8.22A, 1PH, 60HZ ,15A CIRCUIT	60" x 50" x 88"	(1) 46 1/2" x 52 1/2" x 87" (1) 86"x66"x46"	1,741	RCU7BCF	BCH0076M*ABXX0	WS0751M6*AP
AP36BCF-2T	BLAST CHILLER & SHOCK FREEZER	(2) 31" x 38" x 73.5"	720	432	88000	MEDIUM / LOW TEMP	208 VAC, 15.5A, 1PH, 60HZ ,20A CIRCUIT	60" x 94" x 88"	(1) 46 1/2" x 52 1/2" x 87" (1) 96"x66"x60"	2,429	RCU12BCF	BLV120BM6*AP	WS1200M6*AP
AP36BCF-3T	BLAST CHILLER & SHOCK FREEZER	(3) 31" x 38" x 73.5"	1080	648	132000	MEDIUM / LOW TEMP	208 VAC, 22.7A, 1PH, 60HZ ,30A CIRCUIT	60" x 152" x 89"	(2) 46 1/2" x 52 1/2" x 87" (1) 86"x66"x74"	3,484	RCU22BCF	BCV0220M*ABXX0	WS2200M6*AP
AP46BC-1T	BLAST CHILLER	(1) 35" x 39" x 73.5"	460	N/A	70000	MEDIUM TEMP	208 VAC, 8.22A, 1PH, 60HZ ,15A CIRCUIT	64" x 51" x 88"	(1) 46 1/2" x 52 1/2" x 87" (1) 86"x66"x46"	1,810	RCU12BC	BCH0120M*ACDX0	WS1200M6*
AP46BC-1T-CP SM	BLAST CHILLER	(1) 35" x 39" x 73.5"	460	N/A	70000	MEDIUM TEMP	208 VAC, 8.22A, 1PH, 60HZ ,15A CIRCUIT	61" x 41" x 83"	(1) 46 1/2" x 52 1/2" x 87" N/A	694	RCU12BC	BCH0120M*ACDX0	WS1200M6*
AP46BC-2T	BLAST CHILLER	(2) 35" x 39" x 73.5"	920	N/A	120000	MEDIUM TEMP	208 VAC, 15.5A, 1PH, 60HZ ,20A CIRCUIT	64" x 96" x 88"	(1) 46 1/2" x 52 1/2" x 87" (1) 98"x66"x60"	2,561	RCU25BC	BCV0250M*ACDX0	WS2500M6*
AP46BC-2T-CP SM	BLAST CHILLER	(2) 35" x 39" x 73.5"	920	N/A	120000	MEDIUM TEMP	208 VAC, 15.5A, 1PH, 60HZ ,20A CIRCUIT	61" x 86" x 83"	(1) 46 1/2" x 52 1/2" x 87" N/A	1,004	RCU25BC	BCV0250M*ACDX0	WS2500M6*
AP46BC-3T	BLAST CHILLER	(3) 35" x 39" x 73.5"	1380	N/A	180000	MEDIUM TEMP	208 VAC, 22.7A, 1PH, 60HZ ,30A CIRCUIT	64" x 155" x 89"	(2) 46 1/2" x 52 1/2" x 87" (1) 86"x66"x74"	3,655	RCU25BC	BCV0250M*ACDX0	WS2500M6*
AP46BC-3T-CP SM	BLAST CHILLER	(3) 35" x 39" x 73.5"	1380	N/A	180000	MEDIUM TEMP	208 VAC, 22.7A, 1PH, 60HZ ,30A CIRCUIT	61" x 131" x 83"	(2) 46 1/2" x 52 1/2" x 87" N/A	1,682	RCU25BC	BCV0250M*ACDX0	WS2500M6*
AP46BCF-1T	BLAST CHILLER & SHOCK FREEZER	(1) 35" x 39" x 73.5"	460	276	70000	MEDIUM / LOW TEMP	208 VAC, 8.22A, 1PH, 60HZ ,15A CIRCUIT	64" x 51" x 88"	(1) 46 1/2" x 52 1/2" x 87" (1) 86"x66"x46"	1,810	RCU12BCF	BLV120BM6*AP	WS1200M6*AP
AP46BCF-1T-CP SM	BLAST CHILLER & SHOCK FREEZER	(1) 35" x 39" x 73.5"	460	276	70000	MEDIUM / LOW TEMP	208 VAC, 8.22A, 1PH, 60HZ ,15A CIRCUIT	61" x 38" x 83"	(1) 46 1/2" x 52 1/2" x 87" N/A	694	RCU12BCF	BLV120BM6*AP	WS1200M6*AP
AP46BCF-2T	BLAST CHILLER & SHOCK FREEZER	(2) 35" x 39" x 73.5"	920	552	120000	MEDIUM / LOW TEMP	208 VAC, 15.5A, 1PH, 60HZ ,20A CIRCUIT	64" x 96" x 88"	(1) 46 1/2" x 52 1/2" x 87" (1) 98"x66"x60"	2,561	RCU22BCF	BCV0220M*ABXX0	WS2200M6*AP
AP46BCF-2T-CP SM	BLAST CHILLER & SHOCK FREEZER	(2) 35" x 39" x 73.5"	920	552	120000	MEDIUM / LOW TEMP	208 VAC, 15.5A, 1PH, 60HZ ,20A CIRCUIT	61" x 86" x 83"	(1) 46 1/2" x 52 1/2" x 87" N/A	1,004	RCU22BCF	BCV0220M*ABXX0	WS2200M6*AP
AP46BCF-3T	BLAST CHILLER & SHOCK FREEZER	(3) 35" x 39" x 73.5"	1380	828	180000	MEDIUM / LOW TEMP	208 VAC, 22.7A, 1PH, 60HZ ,30A CIRCUIT	64" x 155" x 89"	(2) 46 1/2" x 52 1/2" x 87" (1) 86"x66"x74"	3,655	RCU30BCF	BCV0300M*ABXX0	WS3000M6*AP
AP46BCF-3T-CP SM	BLAST CHILLER & SHOCK FREEZER	(3) 35" x 39" x 73.5"	1380	828	180000	MEDIUM / LOW TEMP	208 VAC, 22.7A, 1PH, 60HZ ,30A CIRCUIT	61" x 131" x 83"	(2) 46 1/2" x 52 1/2" x 87" N/A	1,682	RCU30BCF	BCV0300M*ABXX0	WS3000M6*AP

<sup>1</sup> - 160°F TO 38°F WITHIN 90 MIN      <sup>2</sup> - 160°F TO 0°F WITHIN 240 MIN      <sup>3</sup> - AT EVAP. TEMP. 14°F AND COND. TEMP. 105°      <sup>4</sup> - REQUIRED INTERIOR DIMENSION FOR THE CABINET ON THE "-CP" MO

\*- INSERT "C" FOR 208-230V/60HZ/3PH MODELS, INSERT "D" FOR 460V/60HZ/3PH MODELS      \*\*- INSERT "3" FOR 208-230V/60HZ/3PH MODELS, INSERT "4" FOR 460V/60HZ/3PH MODELS

SHIPPING WEIGHTS DO NOT INCLUDE CONDENSING UNITS      SHIPPING WEIGHTS DO NOT INCLUDE PANELS FOR THE "-CP" MODELS

# AMERICAN PANEL HURRICHILL CONDENSING UNITS

MODEL NUMBER	REQ'D BTU/H*	REFRIG.	SUCTIO N LINE	LIQUID LINE	WATER LINE	GPM @15F SST	PSI DROP WATER	DIMENSIONS LxWxH	NET WEIGHT [LBS]	SHIPPING WEIGHT [LBS]	ELECTRICAL SUPPLY	MANUF. MODEL	COMPRESSOR MODEL AND TYPE	RECEIVER CAPACITY
<b>MED TEMP AIR COOLED</b>														
RCU4BC-A	32410	R404A	1 1/8"	1/2"	N/A	N/A	N/A	43 7/8" X 30 1/2" X 29 1/4"	327	360	208-230V / 60HZ / 3PH; 21.9A, MCA 27, MOPD 40 460V / 60HZ / 3PH ; 11A, MCA 15, MOPD 20	BCH0045MCACZX0 BCH0045MDACZX0	ZS29KAE COPELAND SCROLL	40 LBS @ 90%
RCU6.5BC-A	43730	R404A	1 1/8"	1/2"	N/A	N/A	N/A	43 7/8" X 30 1/2" X 29 1/4"	335	360	208-230V / 60HZ / 3PH; 25A, MCA 30.3, MOPD 50 460V / 60HZ / 3PH ; 10.2A, MCA 15, MOPD 20	BCH0060MCACZX0 BCH0060MDACZX0	ZS45K4E COPELAND SCROLL	40 LBS @ 90%
RCU6BC-A	50960	R404A	1 1/8"	1/2"	N/A	N/A	N/A	51 5/8" X 36 3/4" X 39 3/16"	761	914	208-230V / 60HZ / 3PH; 31A, MCA 38.1, MOPD 60 460V / 60HZ / 3PH ; 14.3A, MCA 17.4, MOPD 25	BCH0075MCACDX BCH0075MDACDX	2DL3R78KE DISCUS	52 LBS @ 90%
RCU7BC-A	62560	R404A	1 3/8"	5/8"	N/A	N/A	N/A	63 5/8" X 35 5/8" X 39 1/8"	985	1148	208-230V / 60HZ / 3PH; 34.1A, MCA 41.3, MOPD 70 460V / 60HZ / 3PH ; 16.4A, MCA 20, MOPD 30	BCH0076MCACDX BCH0076MDACDX	2DA3R89KE DISCUS	78 LBS @ 90%
RCU12BC-A	99680	R404A	1 3/8"	5/8"	N/A	N/A	N/A	63 5/8" X 36 3/8" X 39 1/8"	1065	1228	208-230V / 60HZ / 3PH; 48.6A, MCA 59.4, MOPD 100 460V / 60HZ / 3PH ; 25A, MCA 32.2, MOPD 50	BCH0120MCACDX BCH0120MDACDX	3DF3R15ME DISCUS	78 LBS @ 90%
RCU15BC-A	117540	R404A	1 5/8"	7/8"	N/A	N/A	N/A	75 1/8" X 41 3/4" X 48 3/4"	1182	1442	208-230V / 60HZ / 3PH; 62.3A, MCA 90.7, MOPD 125 460V / 60HZ / 3PH ; 30.4A, MCA 36.9, MOPD 60	BCH0150MCACDC BCH0150MDACDC	3DS3R17ME DISCUS	98 LBS @ 90%
RCU25BC-A	161580	R404A	2 1/8"	1 1/8"	N/A	N/A	N/A	170 11/16" X 48 7/8" X 53	1770	2100	208-230V / 60HZ / 3PH; 80.8A, MCA 90.5, MOPD 150 460V / 60HZ / 3PH ; 40.4A, MCA 50, MOPD 80	BCV0250MCACDX BCV0250MDACDX	4DHNR22ME	123 LBS @ 90%
<b>MED TEMP WATER COOLED</b>														
RCU4BC-W	30950	R404A	7/8"	1/2"	1/2"	7.7	3.2	36" X 34" X 28 5/8"	207	265	208-230V / 60HZ / 3PH; 18.4A, MCA 23, MOPD 40 460V / 60HZ / 3PH ; 8.4A, MCA 15, MOPD 15	ZWN045X6C ZWN045X6D	ZS29KAE COPELAND SCROLL	20 LBS @ 90%
RCU6.5BC-W	45115	R404A	7/8"	1/2"	3/4"	10.8	2.9	36" X 34" X 28 5/8"	241	299	208-230V / 60HZ / 3PH; 21.5A, MCA 26.9, MOPD 45 460V / 60HZ / 3PH ; 8.3A, MCA 15, MOPD 15	ZWN060X6C ZWN060X6D	ZS45K4E COPELAND SCROLL	20 LBS @ 90%
RCU7BC-W	60580	R404A	1 3/8"	5/8"	1 1/4"	13.9	3.5	47" X 35 3/8" X 43 1/2"	615	790	208-230V / 60HZ / 3PH; 28.7A, MCA 35.9, MOPD 60 460V / 60HZ / 3PH ; 12.6A, MCA 20, MOPD 25	SWN0760M6C SWN0760M6D	2DA3R89KE DISCUS	60 LBS @ 90%
RCU6BC-W	0	R404A							0	0	208-230V / 60HZ / 3PH; A, MCA , MOPD	SWN075M6C SWN075M6D		
RCU12BC-W	103030	R404A	1 5/8"	7/8"	1 1/4"	23.2	.9	56" X 31" X 33 3/4"	701	850	208-230V / 60HZ / 3PH; 43.2A, MCA 54, MOPD 90 460V / 60HZ / 3PH ; 21.2A, MCA 26.5, MOPD 45	WS1200M6C WS1200M6D	3DF3R15ME DISCUS	147 LBS @ 90%
RCU15BC-W	117310	R404A	1 5/8"	7/8"	1 1/2"	25.6	0.8	47" X 35 3/8" X 43 1/2"	615	790	208-230V / 60HZ / 3PH; 53.5A, MCA 66.9, MOPD 110 460V / 60HZ / 3PH ; 26A, MCA 32.5, MOPD 50	SWN1500M6C SWN1500M6D	3DS3R17ME DISCUS	125 LBS @ 90%
RCU25BC-W	154000	R404A	2 1/8"	1 1/8"	2 1/2"	34.8	1.1	67 1/4" X 36 1/2" X 44	1189	1400	208-230V / 60HZ / 3PH; 66.8A, MCA 83.5, MOPD 150 460V / 60HZ / 3PH ; 33.4A, MCA 41.8, MOPD 70	WS2500M6C WS2500M6D	4DHNR22ME	182 LBS @ 80%
<b>MED/LOW TEMP AIR COOLED</b>														
RCU3BCF-A	31360	R404A	1 1/8"	1/2"	N/A	N/A	N/A	63 3/4" X 36 3/4" X 39 1/4"	775	900	208-230V / 60HZ / 3PH; 22.3A, MCA 26.5, MOPD 40 460V / 60HZ / 3PH ; 11A, MCA 15, MOPD 20	BBT0301M6CAP BBT0301M6DAP	2DES-3 BITZER SEMI-HERMETIC	67 LBS @ 80%
RCU6BCF-A	52260	R404A	1 3/8"	5/8"	N/A	N/A	N/A	63 3/4" X 36 3/4" X 39 1/4"	823	1000	208-230V / 60HZ / 3PH; 36.4A, MCA 44.2, MOPD 70 460V / 60HZ / 3PH ; 17.2A, MCA 20.6, MOPD 30	BCH0056MCABXX0 BCH0056MDABXX0	4EES-6-2DU-1Y SEMI-HERMETIC	78 LBS @ 90%
RCU7BCF-A	63789	R404A	1 3/8"	5/8"	N/A	N/A	N/A	75 1/4" X 41 3/4" X 48 3/4"	935	1200	208-230V / 60HZ / 3PH; 40A, MCA 48.2, MOPD 80 460V / 60HZ / 3PH ; 19.7A, MCA 22.1, MOPD 35	BCH0076MCABXX0 BCH0076MDABXX0	4DES-7 BITZER SEMI-HERMETIC	67 LBS @ 80%
RCU12BCF-A	97596	R404A	1 5/8"	7/8"	N/A	N/A	N/A	144" X 44 1/2" X 55 5/8"	1400	1980	208-230V / 60HZ / 3PH; 54.4A, MCA 66.1, MOPD 110 460V / 60HZ / 3PH ; 25A, MCA 30.3, MOPD 50	BLV120BM6CAP BLV120BM6DAP	4TE-12-2NU BITZER SEMI-HERMETIC	123 LBS @ 80%
RCU22BCF-A	149617	R404A	2 1/8"	1 1/8"	N/A	N/A	N/A	170 3/4" X 44 3/8" X 53 7/8"	1700	2075	208-230V / 60HZ / 3PH; 82A, MCA 92.1, MOPD 150 460V / 60HZ / 3PH ; 37.8A, MCA 41.9, MOPD 70	BCV0220MCABXX0 BCV0220MDABXX0	4JE-22-2NU BITZER SEMI-HERMETIC	123 LBS @ 80%
RCU30BCF-A	201623	R404A	2 1/8"	1 1/8"	N/A	N/A	N/A	225 3/4" X 44 1/2" X 55 5/8"	1715	2225	208-230V / 60HZ / 3PH; 120.2A, MCA 145, MOPD 225 460V / 60HZ / 3PH ; 55.4A, MCA 67.4, MOPD 110	BCV0300MCABXX0 BCV0300MDABXX0	4GE-30-2NU BITZER SEMI-HERMETIC	188 LBS @ 80%
<b>MED/LOW TEMP WATER COOLED</b>														
RCU3BCF-W	34100	R404A	1 1/8"	1/2"	1 1/4"	8	1.8	32 1/2" X 23 7/8" X 28"		420	208-230V / 60HZ / 3PH; 16.9A, MCA 21.1, MOPD 35 460V / 60HZ / 3PH ; 7.2A, MCA 15, MOPD 15	WS0301M6CAP WS0301M6DAP	2DES-3 BITZER SEMI-HERMETIC	35 LBS @ 90%
RCU7BCF-W	69100	R404A	1 3/8"	5/8"	1 1/4"	14.7	4	44 3/8" X 24" X 28 1/4"	0	547	208-230V / 60HZ / 3PH; 34.2A, MCA 42.8, MOPD 70 460V / 60HZ / 3PH ; 15.3A, MCA 20, MOPD 30	WS0751M6CAP WS0751M6DAP	4DES-7 BITZER SEMI-HERMETIC	53 LBS @ 90%
RCU6BCF-W	53510	R404A	1 3/8"	5/8"	1 1/4"	16.8	1.8	45 15/16" X 35 9/16" X 29	425	550	208-230V / 60HZ / 3PH; 31A, MCA 38.8, MOPD 60 460V / 60HZ / 3PH ; 13.4A, MCA 20, MOPD 30	WS0750M6C*SP WS0750M6D*SP	4EES-6-2DU-1Y SEMI-HERMETIC	45 LBS @ 80%
RCU12BCF-W	106000	R404A	1 5/8"	7/8"	1 1/2"	25.2	0.8	56 1/8" X 24" X 32 1/2"	0	595	208-230V / 60HZ / 3PH; 46.8A, MCA 58.5, MOPD 100 460V / 60HZ / 3PH ; 21.2A, MCA 26.5, MOPD 45	WS1200M6CAP WS1200M6DAP	4TE-12-2NU BITZER SEMI-HERMETIC	111 LBS @ 90%
RCU22BCF-W	162400	R404A	2 1/8"	7/8"	2 1/2"	34.7	1.1	66 9/16" X 36 1/2" X 34 1/4"	0	743	208-230V / 60HZ / 3PH; 68A, MCA 85, MOPD 150 460V / 60HZ / 3PH ; 30.8A, MCA 38.5, MOPD 60	WS2200M6CAP WS2200M6DAP	4JE-22-2NU BITZER SEMI-HERMETIC	205 LBS @ 90%
RCU30BCF-W	219480	R404A	2 1/8"	1 1/8"	2 1/2"	47.1	1.1	66 1/2" X 36 1/2" X 36 1/2"	0	755	208-230V / 60HZ / 3PH; 99.2A, MCA 124, MOPD 200 460V / 60HZ / 3PH ; 44.9A, MCA 56.1, MOPD 100	WS3000M6CAP WS3000M6DAP	4GE-30-2NU BITZER SEMI-HERMETIC	205 LBS @ 90%

\* - AT 15°F SST AND 95°F AMBIENT / 85°F EWT