

BLAST CHILLER MODEL	REQUIRED BTU/Hr	COND UNIT MODEL (BOHN MODEL) 230 VOLT
AP20BC-1T	28,000	BZT045M6C
AP20BC-2T	56,000	BDT0751M6C
AP20BC-3T	84,000	BDT1200M6C
AP20BCF-1T	28,000	BBT0301M6CAP
AP20BCF-2T	56,000	BBT0751M6CAP
AP20BCF-3T	84,000	BLV120BM6CAP
AP26BC-1T	34,000	BZT060M6C
AP26BC-1T-CP	34,000	BZT060M6C
AP26BC-2T	68,000	BDT1200M6C
AP26BC-2T-CP	68,000	BDT1200M6C
AP26BC-3T	102,000	BDT1500M6C
AP26BC-3T-CP	102,000	BDT1500M6C
AP26BCF-1T	34,000	BBT0551M6C
AP26BCF-1T-CP	34,000	BBT0551M6C
AP26BCF-2T	68,000	BLV120BM6CAP
AP26BCF-2T-CP	68,000	BLV120BM6CAP
AP26BCF-3T	102,000	BLV220BM6CAP
AP26BCF-3T-CP	102,000	BLV220BM6CAP
AP36BC-1T	44,000	BDT0751M6C
AP36BC-2T	88,000	BDT1200M6C
AP36BC-3T	132,000	BLV2500M6C
AP36BCF-1T	44,000	BBT0751M6CAP
AP36BCF-2T	88,000	BLV120BM6CAP
AP36BCF-3T	132,000	BLV220BM6CAP
AP46BC-1T	70,000	BDT1200M6C
AP46BC-1T-CP	70,000	BDT1200M6C
AP46BC-2T	120,000	BLV2500M6C
AP46BC-2T-CP	120,000	BLV2500M6C
AP46BC-3T	180,000	BLV2500M6C
AP46BC-3T-CP	180,000	BLV2500M6C
AP46BCF-1T	70,000	BLV120BM6CAP
AP46BCF-1T-CP	70,000	BLV120BM6CAP
AP46BCF-2T	120,000	BLV220BM6CAP
AP46BCF-2T-CP	120,000	BLV220BM6CAP
AP46BCF-3T	180,000	BLV300BM6CAP
AP46BCF-3T-CP	180,000	BLV300BM6CAP