



Name: _____
Company: _____
Address: _____
Phone: _____
Fax #: _____

Date: _____
Job: _____
Location: _____
Marketing Agent: _____
APC Sales Associate: _____

TYPE OF ROOM: Cooler Beer Cooler Freezer Combination Other
NOMINAL OVERALL SIZE (Outside Dimensions): Width Length Height
ACTUAL OVERALL SIZE (Outside Dimensions): Width Length Height
COMBINATION: Cooler (W x L) Freezer (W x L) Other (W x L)
INSTALLATION: Inside Outside (Go To Outdoor Accessories Section) CONSTRUCTION: NSF
INSULATION: 4" Foamed-In-Place Urethane, UL Flame Spread 20 5" Foamed-In-Place Urethane, UL Flame Spread 20

FLOOR:
Without Floor (Vinyl Screed Provided)
Cooler Floorless/Freezer with Floor (Select Type)
.100 Smooth Aluminum
14 Ga. Galvanized Steel (non-NSF)
1/8" Diamond Aluminum Treadplate Floor Surface
16 Ga. Stainless Steel With Non-Skid Strips in Aisle
1/8" Diamond Aluminum Treadplate Overlay on Galv. Steel
3/16" Diamond Aluminum Treadplate Overlay on Galv. Steel
AmeriTuff Structural Flooring
Insulated Slab by Others. Insulation by: APC Others

ACCESSORIES:
System 100 Monitoring System (Standard)
System 200 Monitoring System
Heated Pressure Relief Vent
Extra Vapor Proof Lights: Qty.
4' Fluorescent Lights: Qty.
LED Lighting (Replacing Vapor Proof/Fluorescents)
Roof Support Channel (Indoor Only)
Interior Support Steel Structure
Closure Panel
Trim Strips
Bumper Rail, 22 Ga. Stainless Steel
Bumper Rail, Vinyl with Aluminum Extrusion
Wall Protection
Other

Table with columns: FINISH, INT., EXP., UNEXP., EXT.
Rows include: 26 Ga. Stucco Acrylume, .032 Stucco Emb. Aluminum, .040 Stucco Emb. Aluminum, .040 White Stucco Aluminum, .040 Smooth White Aluminum, 26 Ga. Stucco White Steel, 20 Ga. Smooth White Galv. Steel, 24 Ga. Smooth Galv. Steel, 22 Ga. Stucco Stainless Steel, 22 Ga. Stainless Steel, 20 Ga. Stainless Steel

OUTDOOR ACCESSORIES:
Rain Roof, Vinyl Membrane Type
Flat Pitched One-Way Pitched Two-Way
Door Locking Bar Door Rain Cap
Hurricane Code Floor Angle

REFRIGERATION:
Condensing Unit Location: Indoor Outdoor
On Slab On Building Roof On Walk-In Roof
Sized for: Holding Only Specified BTUH/HP
Hermetic Scroll Semi-Hermetic
Air Cooled Water Cooled
Basic Remote
Remote Quick Connect ft. Precharged Lines (40' Max)
Top Quick Connect (Roof Penetration)
Top Quick Connect (Wall Penetration)
Pre-Assembled Remote
Deluxe Pre-Assembled Remote (includes stand)
By Others

WALK-IN DOORS:
Standard Size Flush Door Cooler Qty: Freezer Qty:
Special Size Flush Door Cooler Qty: Freezer Qty:
Size: _____

VOLTAGE:
115/60/1 208/60/1 230/60/1
208/230/60/3 Other _____

OPTIONAL HARDWARE:
Kickplate Int. Ext. Ht:
Ramp Int. Ext.
Heated View Window Thermal Strip Curtain
Deadbolt Lock Spring Loaded Hinge
Deadbolt Lock w/ Institutional Handle Extra Hinge
3-Way Light Switch
Foot Treadle
Other: _____

REFRIGERATION ACCESSORIES:
Compressor Cover Winterization Controls
12" High Comp. Stand UL Outdoor Cover
Pitch Pans 18" High Comp. Stand
Mounting Curbs Other
One Year Service on Pre-Charged Systems
5-Year Warranty Deduct (Outside of U.S.)

SPECIAL DOORS:
Hinged Solid Reach-In Qty. Width Height
Hinged Glass Qty. Width Height
Lights Shelves Heaters
Sliding Glass Qty. Width Height
Insulated Sliding Doors Qty. Width Height
Manual Electric
Single Slide Bi-Parting Slide